DirectTex®
Flag Supreme

Fields of application

.02 .04 .05 .06 .07

Specifications

REF. 599096 141

100 % polyester
knit fabrics
PVC-free, recyclable

ca. 160/ 252/ 320/ 505 cm
ca. 63/ 99/ 126/ 199 inch
other widths available on request

B-s1, d0 DIN EN 13501-1

ca. 90 g/m²
ca. 2.65 oz/yd²

ca. 0.28 mm
ca. 280 µm

rolls
100 m
109 yd

Light
blank: 55.8 %
DIN EN 410

length: 395.8 N (15.4 N)
cross: 425.2 N (15.3 N)
DIN EN ISO 13934-1 (13934-2)

length: 23.5 %
cross: 64.2 %
DIN EN ISO 13934-1

length: 0.7 %
cross: 12.4 %
DIN EN 14704-1

Specs
UV stable

cold, heat, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

Article shrinkage
(50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,4 %	1,2 %	•
190°C	0,5 %	1,2 %	
200°C	0,6 %	1,2 %	
210°C	0,7 %	1,5 %	

Certifications

OEKO TEX® STANDARD 100 09.0.67573 Hohenstein HTTI

PONGS GROUP GMBH & CO. KG
Bahnhofstraße 21
07919 Pausa-Mühltroff
Germany
Phone +49 36645 350-0
salestt@pongs.com
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of ± 5% is valid. Effective: 2024/03

DirectTex®
Flag Supreme

Fields of application

.02 .04 .05 .06 .07

Ref.-Nr.: 599096 141 | Preview print sample

PONGS GROUP GMBH & CO. KG
Bahnhofstraße 21
07919 Pausa-Mühltroff
Germany
Phone +49 36645 350-0
salestt@pongs.com
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of ± 5% is valid. Effective: 2024/03