

EMBLEM Polypropylen Lamination Film Glossy 50

EMBLEM Polypropylene Lamination Film Glossy 50 is a glossy protective laminate for print finishing in the graphic industry. The even gloss level enhances the contrast in the printing. The pressure sensitive adhesive allows a fast and effective processing when laminating from roll.

Matchcode:	POPLAMGL50
Material:	polypropylene
Finish:	glossy
Colour:	transparent
Thickness:	50 μm
Liner:	one-side siliconised kraft paper, 120 g/m ²
Adhesive:	transparent, permanent, polyacrylate
Adhesion power:	19,8 N / 25 mm acc. FINAT 1 - 24h contact (average value)
Temperature resistance:	-20 °C to +40 °C
Application temperature:	min. +15 °C
Fire behaviour:	not tested
Durability:	24 month indoor, short term outdoor
Standard roll width:	1050 / 1370 mm
Standard roll length:	50 m
Lamination film:	face out
Storage:	cool and dry environment, at 15-25 °C, 50 % rel. humidity
Shelf life:	24 month in original boxes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 4193-9950 · Telefax: +49 4193-995220 E-Mail: info@dataplot.de · Internet: www.dataplot.de