

EMBLEM Solvent Magic Grip Clear Neo III

EMBLEM Solvent Magic Grip Clear Neo III is based on a transparent polyester film. Thanks to its magic adhesive, the film clings to smooth surfaces, is easy to apply and can be removed without leaving any residue. Typical applications are short-term advertising at the POS and interior decorations.

Matchcode:	SOMAGRICLN3
Material:	coated polyester film
Finish:	glossy
Color:	transparent
Thickness:	125 $\mu\text{m} \pm 10$
Weight:	160 $\text{g/m}^2 \pm 10$
Liner:	PET film, translucent, 50 μm
Application temperature:	> +10 °C
Standard roll width:	1370 mm
Standard roll length:	30 m
Durability:	short term indoor applications, up to 12 months
Storage:	cool and dry environment, at 15-25 °C, 50 % rel. humidity
Shelf life:	12 months in original packing

COMPATIBLE INKS:

Eco Solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Solvent Magic Grip Clear Neo III

Despriction:

EMBLEM Solvent Magic Grip Clear Neo III is based on a transparent polyester film with a glossy coating that can be printed with common eco solvent, solvent, latex and UVC inks. Objects behind the film are displayed very sharply due to its clarity. Thanks to the innovative Magic adhesive technology, EMBLEM Solvent Magic Grip Clear Neo III adheres to smooth surfaces such as glass. The film is easy to apply and can still be repositioned and removed without leaving any residue.

Processing:

The film adheres only on smooth, flat or cylindrical surfaces like windows. The subsurfaces which are to be pasted up have to be free of dust and grease. The user is advised to make tests before application to check compatibility between film and subsurface. If the adhesive surface is polluted by dust, it can be cleaned carefully with clear water.

When applying, the liner can be placed between the print and the squeegee to protect the print.

For bubble-free adhesion, the substrate can be sprayed with a little clear water. This must then be carefully squeegeed out. Changes in transparency after wet application can last up to 48 hours.

To avoid fingerprints the use of cotton gloves is advised.

Application:

Typical indoor-applications are short term promotions, shop window advertising and interior design.